



# Grout mixing pump

PH9B-P

Designed on the basis of solutions recognized for many years to be reliable, simple and robust. Optimized for grout pumping, micropiles, filing and patch screeding.

STAGE 



- Machine fully designed using reliable and known technical solutions
- Patented dust extraction system, very efficient as it is directly connected to the the mixer bin
- 245 L XXL mixer (optional), for even a higher performance level
- Perfect water system to set-up and control the water dosage in all simplicity
- Optimal weight balance on the drawbar for better manoeuvrability on jobsite
- Skid version also available (on request)
- Less maintenance time with the main components freely and easily accessible

# Grout mixing pump

**PH9B-P**



## USER SAFETY

- Dust extraction system = 95% less dust
- Low noise emission
- Very good balance, drive axle without brake
- Skid version optimized for cranes and forklifts



## USER COMFORT

- Compact machine, easy to handle with low loading height
- Sucking water pump directly connected to the mixer and the HPC
- Simple water meter system with digital display
- Integrated high pressure cleaner (HPC) in option



## MANPOWER GAIN

- Hydraulic drives mixer, effortless and optimal safety
- Large volume mixer (XXL version) available in option
- Low costs of ownership. Robust machine with reliable components

## TECHNICAL COMFORT

- Complete equipment to ensure perfect material mixing and pumping
- Ergonomic, full, waterproof and centralized control panel
- 2-way remote control in compliance with European Directive 2006/42/CE in option



## DELIVERED BY

### Strata

2b Stephenstown Industrial Park, Balbriggan,  
County Dublin, Ireland K32 KV26

**UK** 01895 276751

**Ireland** 01 690 3162

**International** +353 1690 3162

TECHNICAL SPECIFICATIONS	PH9B-P
<b>Theoretical flow rate (*)</b>	60 L/min max. (with 2L61 pump) 100 L/min max. (with 1,5L63 pump)
<b>Maximum grain size</b>	6 mm
<b>Discharge distance (**)</b>	100 m horizontally, 40 m vertically
<b>Stage V Engine</b>	Liquid-cooled Kubota engine 3-cyl 15.5 kW
<b>Mixer</b>	Hydraulic drives
	Capacity 180 L or 245 L (XXL option)
	Loading height 0,95 m
<b>Pumping hopper capacity</b>	220 L
<b>Worm pump</b>	2L61 or 1,5L63
<b>Safety</b>	Automatic on opening of the mixer and feeder hopper grids
<b>Sound power</b>	< 99 LWA
<b>Axle</b>	Unbrake, road approval
<b>Weight (road version)</b>	< 750 kg
<b>Dimensions (road version)</b>	3255 x 1440 x 1237 mm (L x l x h)
<b>Dimensions (skid version)</b>	2985 x 1515 x 1250 mm (L x l x h)
<b>No rendering, machine without compressor</b>	

\* The delivery rate is theoretical and depends on the pumping material properties and jobsite configuration.

\*\* No-cumulative, maximum distances and depend on pumping material properties.



PL2M • Parc d'activités - 26 Avenue des Mondaults - 33270 Floirac  
www.lancy.com • info@lancy.com

