



Rendering machine

PH9B-R

New model rendering machine PH9B-R with lifting mixer. New design and technical optimization of a recognized solution since many years for its comfort, manoeuvrability and reliability.

STAGEV



- Machine fully designed using reliable and known technical solutions
- Patented dust extraction system, very efficient as it is directly connected to the the mixer bin
- 245 L XXL mixer (optional), for even a higher performance level
- Simple and user-friendly control panel and water meter system
- Optimal balance on the drawbar for better manoeuvrability on jobsite
- Less maintenance time with the main components freely and easily accessible
- Back side completely redesigned avec LED lights and bumper for side and rear protections
- Low operating cost

Rendering machine

PH9B-R



USER SAFETY

- Dust extraction system = 95% less dust
- Low noise emission
- Very good balance, drive axle without brake
- Low loading height

USER COMFORT

- Machine compact, easy to handle with low loading height
- Ergonomic, full, waterproof and centralized control panel
- Adjustable spray flow rate
- Simple water meter system with digital display
- High pressure cleaner (in option). Can be used simultaneously when pumping.

MANPOWER GAIN

- Complete equipment to ensure perfect material mixing and pumping
- Hydraulic drives lifting mixer, effortless and optimal safety
- Large volume mixer (XXL version) available in option
- Low costs of ownership. Robust machine with reliable components
- Handles on the mixer grid, easy to open and better manoeuvrability
- Two rearming buttons

CREATIVE TECHNOLOGY

- Optimized compressor system for optimal reliability
- Automatic compressor belt tension
- Compressor venting = full load only while spraying
- Engine + compressor on silent blocks = no vibration
- New mortar hoses with larger internal diameter
- Nouveau control panel with service warning
- New plug and play diesel filtration



TECHNICAL SPECIFICATIONS	PH9B-R
Theoretical flow rate (*)	60 L/min max. (with 2L61) • 100 L/min max. (with 1,5L63 p)
Maximum grain size	6 mm
Discharge distance (**)	L 100 m / H 40 m
Stage V engine	Liquid-cooled Kubota engine 3-cyl 15,5 kW
Mixer	Hydraulic drives
	Capacity 180 L or 245 L (XXL option)
	Loading height 0,95 m
Pumping hopper capacity	220 L
Worm pump	2L61 or 1,5L63
Pumping	Pneumatic control from the spraying nozzle
Twin cylinder compressor	400 L/min
Safety	Automatic on opening of the mixer and feeder hopper grids
Sound power	< 99 IWA
Axle	Unbrake, road approval
Level adjustment	Hand-cranked support stilt
Total weight (all options)	< 750 kg
Dimensions (road version)	3255 x 1440 x 1237 mm (L x l x h)

DISTRIBUTED BY

Strata

2b Stephenstown Industrial Park, Balbriggan,
County Dublin, Ireland K32 KV26

UK 01895 276751

Ireland 01 690 3162

International +353 1690 3162

* The delivery rate is theoretical and depends on the pumping material properties and jobsite configuration.
** No-cumulative, maximum distances and depend on pumping material properties.



PL2M • Parc d'activités - 26 Avenue des Mondaults - 33270 Floirac
www.lancy.com • info@lancy.com

LANCY