

# Liquid floor screed pump

**TF300-D**

Machine compliant with Stage V emission standard, compact, easy to handle, the ideal solution for small and medium-sized jobsites

**STAGE V**



- Machine equipped with diesel engine which complies with Stage V emission standard
- Designed with reliable and high quality components
- Low cost of ownership
- Simple to use. All range of options and equipments available
- Precise output adjustment (5 speeds) with remote control as standard on both models
- Corner grid specially designed for liquid floor screed providing an optimal and consistent material flow
- Perfectly balanced for easy handling on jobsite
- Comfortable road driving with holds the road well

# Liquid floor screed pump

**TF300-D**



## PERFORMANCE AND SIMPLICITY

- High performance machine compliant with Stage V emission standard
- New high quality hydraulic transmission
- Ergonomic remote control and intuitive use
- Lightweight machine, unbrake axle, optimal balance



## LOW COST OF OWNERSHIP

- Competitive purchase price and inexpensive machine using
- Rotor/stator lifespan improvement
- Robust machine, reliable and recognized components
- Few wear parts, fast and simple maintenance



## CREATIVE TECHNOLOGY

- Automatic hoses decompression when stop pumping
- New corner grid suitable with all liquid floor screeds fibers
- Engine efficiency optimization
- Audible pumping stop alarm



## USER COMFORT

- Complete equipments: storage box, HPC, support wheel, stabilizing
- Precise output adjustment (5 speeds) with remote control as standard
- Discontinuous vibrating screen to improve material flow
- Grid choice available and easily replaceable
- Low noise emission when using et reinforced safety



## DISTRIBUTED BY

### Strata

2b Stephenstown Industrial Park, Balbriggan,  
County Dublin, Ireland K32 KV26

UK 01895 276751

Ireland 01 690 3162

International +353 1690 3162

## TECHNICAL SPECIFICATIONS TF300-D

<b>Performances</b>	• Theoretical flow rate (*)	14 m <sup>3</sup> /heure
	• Maximum grain size	8 mm
	• Maximum discharge distance (**)	100 m
<b>Engine</b>	• Liquid-cooled diesel engine	3-cyl. Kubota 18.5 kW Stage V
	• Variable flow hydraulic pump	Rexroth
<b>Pumping</b>	• Discharge hopper capacity	220 L
<b>Capacities</b>	• Diesel tank	25 L
<b>Axle</b>	Unbrake, road approvals	
<b>Dimensions</b>	• L x l x H (mm)	3 317 x 1 530 x 1 180

(\*) The delivery rate is theoretical and depends on the pumping material properties and jobsite configuration.

(\*\*) Maximal distance and depends on pumping materials properties.



PL2M • Parc d'activités - 26 Avenue des Mondaults - 33270 Floirac  
www.lancy.com • info@lancy.com

**LANCY**